

Tanner Window and Door • PAINT Spring 2019

As a member of the 'Verband der Fenster- und Fassadenhersteller (VFF) (Association of Window and Façade Manufacturer) we follow their guidelines and quality control process for stain and paint application along with the coating manufacturer system application requirements.

Coating manufacturer system

We typically use:

Paint:

Manufacturer: Sikkens

- 3 coat application
- Top coat Sikkens Rubbol WF 382

Standard Color

• Any standard RAL or NCS color is a standard color for us. We typically provide a RAL-Color chart to pick the projects color.

Other color option

• We are open to try to match any custom color provided by the Client and an optional choice. Please contact a TWD representative for additional information.

Stain;

Manufacturer: Sikkens

- 3 coat application
- Top coat Sikkens Cetol WF 732

Standard Stain Color

• See 'stain color info sheet' or ask for 'sample wheel'

Other color option

• Custom stain colors are available upon demand

Oils;

Manufacturer: Steinmeyer Natur Oil

- 2 coat application
- Both coats Natural resin-stand oil-mix



Holta 1-Tone Follows the typical paint application

2-Tone (Option)

Comment: in a 2-tone paint scheme, the critical issue to consider is that the interior paint should be the same or more moisture 'resistant' than the exterior paint. If this is not the case, then the risk of exterior paint failure due to moisture pressure from the interior is increased.

